

UTILITY
PATENT APPLICATION
TRANSMITTAL

Attorney Docket No. P00,0677

First Named Inventor or Application Identifier

Manderfield et al.

Express Mail Label No: EL568799295US

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ACCOMPANYING APPLICATION PARTS

1. ☒ Specification Total Pages 13
2. ☒ Drawing(s) (35USC 113) Total Pages 3
3. ☒ Declaration and Power of Attorney Total Pages 3
- a. ☒ Newly executed(original or copy)
- b. ☐ Copy from prior application (37CFR 1.63(d))
(for continuation/divisional with Box 14 completed)
[Note Box 4 Below]
- i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting
Inventor(s) named in the prior application,
see 37 CFR 1.63(d)(2) and 1.33(b).
4. ☐ Incorporation By Reference (usable if Box 3b is checked)
The entire disclosure of the prior application, from which a
copy of the oath or declaration is supplied under Box 3b,
is considered as being part of the disclosure of the
accompanying application and is hereby incorporated by
reference therein.

5. ☒ Assignment Papers (cover sheet & documentation)
6. ☐ Letter under 37 CFR 1.41(c).
7. ☐ English Translation Document (if applicable)
8. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
9. ☐ Preliminary Amendment
10. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
11. ☐ Small Entity ☐ Statement filed in prior application,
Statement(s) Status still proper and desired
12. ☐ Certified Copy of Priority Document(s)
13. ☐ Other: _____

14. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☒ Continuation-in-part (CIP) ☒ of prior application No: 09/543,949

CLAIMS AS FILED

(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) BASIC FEE \$690.00
TOTAL CLAIMS 20	20	0	\$18.00	\$0.00
INDEPENDENT CLAIMS 03	5	2	\$78.00	\$156.00
ANY MULTIPLE DEPENDENT CLAIMS? <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO				
			TOTAL FILING FEE ->	\$846.00

- ☒ The Commissioner is hereby authorized to charge any additional fees which may be required in connection with this application, or credit any overpayment to ACCOUNT NO. 08-2290. A duplicate copy of this sheet is enclosed.
- ☒ A check in the amount of \$ 846.00 to cover the filing fee is enclosed.

15. CORRESPONDENCE ADDRESS

HILL & SIMPSON
A Professional Corporation
233 South Wacker Drive - 85th Floor Sears Tower
Chicago, Illinois 60606
Telephone (312) 876-0200 - Fax (312) 876-0898

SIGNATURE: _____

DATE: June 23, 2000

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

"Express Mail" Mailing Label Number EL568799295US

Date of Deposit: June 23, 2000

I hereby certify that this correspondence is being deposited with the United States Postal "Express Mail Post Office to Addressee" service under 37 CFR 1.10(c) on the date indicated above and is addressed to

**BOX PATENT APPLICATION
COMMISSIONER OF PATENTS AND TRADEMARKS
WASHINGTON, D.C. 20231**

Attorney Docket Number: P00,0677


Title: **MOLDABLE PLASTIC CONTAINER WITH HOURGLASS PROFILE**

Applicant: **Manderfield et al.**

Enclosed are the following documents:

Utility Patent Application Transmittal (in duplicate);
Specification;
Three (3) pages of drawings;
Executed Continuation-in-Part Declaration;
PTO-1595;
Executed Assignment;
Check: \$40.00 (Assignment filing fee);
Check for \$846.00 (filing fee); and

Postcard.



Signature of person mailing documents and fees

SPECIFICATION

TITLE

5 **“MOLDABLE PLASTIC CONTAINER WITH HOURGLASS PROFILE”**

RELATED APPLICATION DATA

10 This application is a continuation-in-part of U.S. Application Serial No. 09/543,949 filed April 6, 2000, the entirety of which is incorporated herein by reference for all purposes and priority is claimed to said application.

FIELD OF THE INVENTION

15 The present invention generally relates to shallow molded plastic containers. More specifically, the present invention relates to a plastic container that is blow molded, injection molded or injection blow molded. Further, the present invention relates to methods for hot-filling and retorting such containers.

BACKGROUND OF THE INVENTION

20 Shallow plastic molded containers are known. However, molded containers with irregular sidewalls that either bulge outward or inward are not generally known because it is difficult to extract such a container in an axial direction from a mold because of the engagement of the irregular sidewall against portions of the mold that correspond to the top or bottom of the container body.

25 Further, while plastic hot-fill containers and plastic retort containers are known, plastic hot-fill containers and plastic retort containers are configured to be deformable or to include expansion members to accommodate volumetric changes of the contents during the cooling of a hot-fill container or during the heating of a retort container. As a result, rigid containers for hot-fill and retort applications are not generally available.

30 Still further, consumer demand requires that new product designs and shapes be constantly developed. This consumer demand also applies to containers such as molded plastic containers. Further, manufacturers are constantly trying to distinguish their products from their competition by creating unique and different packaging, including uniquely designed containers. As a result, there is a need for a moldable plastic container with irregular sidewalls that will present an aesthetically appealing and unique configuration in contrast to prior art molded plastic containers. Containers presenting different and new configurations would be useful to distinguish the products sold in such containers from competing products. Finally, there is a need for molded containers having unique designs that are both rigid and suitable for hot-fill and retort processing.

SUMMARY OF THE INVENTION

The above needs are inventively met by the present invention which provides a plastic molded container that comprises a bowl which includes an upper rim, a bottom and an irregularly shaped sidewall that extends between the upper rim and the bottom. In a preferred embodiment, the sidewall comprises a lower frustum section, a narrow mid-section and an upper frustum section. The lower frustum section connects the bottom of the bowl to the mid-section of the sidewall. The lower frustum section decreases in width as it extends from the bottom of the bowl to the mid-section of the sidewall. In contrast, the upper frustum section connects the upper rim of the bowl to the mid-section of the sidewall. The upper frustum section is upside down or decreases in width as the upper frustum section extends from the upper rim of the bowl to the mid-section of the sidewall.

In an embodiment, the plastic molded container of the present invention further comprises a lid that is securable to the upper rim of the bowl.

In an embodiment, the bowl further comprises a recess disposed between the upper frustum section and the upper rim. In such an embodiment, the lid further comprises a lower lip and the recess of the bowl is adapted to receive the lower lip of the lid.

In an embodiment, the lid is rotatably securable to the rim.

In an embodiment, the container is molded from a plastic selected from the group consisting of polyvinylchloride, polyethyleneterephthalate, high density polyethylene, polycarbonate, polystyrene and polypropylene.

In an embodiment, the molded container of the present invention is blow-molded from a single layer plastic.

In an embodiment, the molded container of the present invention is blow-molded from a multi-layer plastic. In such an embodiment, the multi-layer plastic further comprises at least one gas barrier layer selected from the group consisting of polyvinylidenechloride, nylon, and ethylenevinylalcohol copolymer.

In an embodiment, the molded container of the present invention has a diameter that is greater than its height.

In an embodiment, the bottom of the bowl of the molded container of the present invention includes a downwardly extending circular standing ridge.

In an embodiment, the present invention provides a method for forming a plastic container that comprises the following steps: providing two mold halves, each mold half having a cavity defining one-half of the container which comprises a bowl comprising an upper rim, a bottom and a sidewall extending between the upper rim and the bottom, the sidewall comprising a lower frustum

section, a narrow mid-section and an upper frustum section, the lower frustum section connecting the bottom to the mid-section, the lower frustum section decreasing in width as the lower frustum section extends from the bottom to mid-section, the upper frustum section connecting the upper rim to the mid-section, the upper frustum section decreasing in width as the upper frustum section extends from the upper rim to mid-section; abutting the two mold halves together; blowing plastic material into the abutted mold halves under blow molding conditions; separating the mold halves; and extracting the resultant container.

In an embodiment, the present invention provides a method of forming a plastic container that comprises the following steps: providing a three piece mold, each mold piece having a cavity defining one-third of the container which comprises a bowl comprising an upper rim, a bottom and a sidewall extending between the upper rim and the bottom, the sidewall comprising a lower frustum section, a narrow mid-section and an upper frustum section, the lower frustum section connecting the bottom to the mid-section, the lower frustum section decreasing in width as the lower frustum section extends from the bottom to mid-section, the upper frustum section connecting the upper rim to the mid-section, the upper frustum section decreasing in width as the upper frustum section extends from the upper rim to mid-section; abutting the three mold pieces together; blowing plastic material into the abutted mold pieces under blow molding conditions; separating the mold pieces; and extracting the resultant container.

In an embodiment, the present invention provides a method of hot-filling a container that comprises the following steps: providing a plastic container comprising a bowl comprising an upper rim, a bottom and a sidewall extending between the upper rim and the bottom, the sidewall comprising a lower frustum section, a narrow mid-section and an upper frustum section, the lower frustum section connecting the bottom to the mid-section, the lower frustum section decreasing in width as the lower frustum section extends from the bottom to mid-section, the upper frustum section connecting the upper rim to the mid-section, the upper frustum section decreasing in width as the upper frustum section extends from the upper rim to mid-section; positioning the container within a receptacle; filling the container with material under hot filling conditions; sealing the container with a suitable seal member; and securing a lid on the container.

In an embodiment, the present invention provides a method of retorting material disposed within a container that comprises the following steps: providing a plastic container comprising a bowl comprising an upper rim, a bottom and a sidewall extending between the upper rim and the bottom, the sidewall comprising a lower frustum section, a narrow mid-section and an upper frustum section, the lower frustum section connecting the bottom to the mid-section, the lower frustum

section decreasing in width as the lower frustum section extends from the bottom to mid-section, the upper frustum section connecting the upper rim to the mid-section, the upper frustum section decreasing in width as the upper frustum section extends from the upper rim to mid-section; positioning the container within a receptacle; filling the container with material under ambient or near ambient conditions; securing a lid on the container; sealing the container with a suitable seal member; heating the container, material, lid and seal member.

Other objects and advantages of the present invention will become apparent upon reading the following detailed description and appended claims, and upon reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention, reference should now be made to the embodiments illustrated in greater detail in the accompanying drawings and described below by way of examples of the present invention.

In the drawings:

Figure 1 is a perspective view of a container made in accordance with the present invention;

Figure 2 is a side elevational view of the container shown in Figure 1 and a lid made in accordance with the present invention;

Figure 3 is a bottom perspective view of the container shown in Figures 1 and 2 and further illustrating a mold parting line for a two-piece mold;

Figure 4 is a schematic view illustrating the upper and lower frustum sections of the container design of the present invention;

Figure 5 illustrates, schematically, a bottom plan view of a container made in accordance with the present invention and surrounded by mold halves illustrated by broken lines;

Figure 6 illustrates, schematically, a bottom plan view of a container made in accordance with the present invention and surrounded to three mold pieces of a three-piece mold illustrated by broken lines;

Figure 7 illustrates, schematically, the interior of a mold half and a compressed gas needle used to blow gas into the interior of a parison used to form a container made in accordance with the present invention;

Figure 8 is a bottom perspective view of an alternative embodiment of the container made in accordance with the present invention;

Figure 9 illustrates, schematically, a side plan view of a container made in accordance with the present invention and surrounded by mold lines for a three-piece mold; and

Figure 10 illustrates, schematically, a side plan view of an alternative container surrounded by a three-piece mold.

It should be understood that the drawings are not necessarily to scale and that the embodiments are sometimes illustrated by graphic symbols, phantom lines, diagrammatic representations and fragmentary views. In certain instances, details which are not necessary for an understanding of the invention or which render other details difficult to perceive may have been omitted. It should be understood, of course, that the invention is not necessarily limited to the particular embodiments illustrated herein.

DETAILED DESCRIPTION OF THE PRESENTLY PREFERRED EMBODIMENTS

As illustrated in Figures 1-3, a container 10 embodying the principles of the present invention includes a bowl portion 12 which has a general hourglass configuration and that extends between an upper rim 14 and a bottom 16. The sidewall 12 includes a lower frustum section 18, a mid-section 20 and an upper frustum section 22. The lower frustum section 18 connects the bottom 16 to the mid-section 20 and is upright, or, in other words, decreases in width or diameter as it extends from the bottom 16 to the mid-section 20. The upper frustum section 22 connects the upper rim 14 to the mid-section 20. In contrast to the lower frustum section 18, the upper frustum section 22 is inverted, or, in other words, decreases in width or diameter as it extends from the upper rim 14 to the mid-section 20. In the embodiment illustrated in Figures 1-3, the upper frustum section 22 is shorter than the lower frustum section 18.

As illustrated in Figure 2, the container 10 may also be equipped with a conventional lid 24 that is equipped with an inwardly protruding lip (not shown) that is received in the recess 26 disposed between the upper rim 14 and the upper frustum section 22. As illustrated in Figures 2 and 3, the bottom 16 may be equipped with a circular standing ridge 28 that provides a secure and stable support for the container 10 on a flat surface (not shown).

As may be appreciated from the figures, the container 10 has a maximum width defined by the upper rim 14 or a lower portion of the lower frustum section 18 that is greater than the overall height of the container 10 as measured from the bottom 16 to the top of the upper rim 14.

Referring to Figure 4, the relationship between the upper frustum section 22a and lower frustum section 18a is illustrated in greater detail. The container design 10a consists essentially of two opposing frustum sections, the downwardly extending upper frustum section 22a and the upwardly extending lower frustum section 18a. The inner section of the two frustums is represented by the mid-section 20a. As a result, the container 10a exhibits a general hourglass configuration.

The container 10 of the present invention can be molded from a two piece mold 30 illustrated schematically in Figure 5 and which includes mold halves 32, 34. The mold halves 32, 34 create the parting line 36 illustrated in Figure 3. In contrast, the container 10 can be molded from a three-piece mold 40 which includes mold sections 42, 44 and 46 as illustrated in Figure 6.

Referring to Figure 7, the presently preferred method for forming the container 10 includes the use of plastic parison material 50 that is captured in a cavity 52 defined by the two mold halves 32, 34 illustrated in Figure 5. Compressed gas is blown into the mold 30 to force the parison material 50 against the walls of the cavity 52 defined by the mold halves 32, 34. The container 10 is then formed in the normal manner with the appropriate cooling steps, such as liquid cooling to set the shape of the plastic material. When the container 10 is completed, the mold halves 32, 34 are separated and the container 10 is ejected or released.

Blow molding is well known to those skilled in the art and reference can be made to United States Patent Nos. 4,457,855 and 4,990,382, which are incorporated herein by reference.

As illustrated in Figure 4, a spin trim dome or a blow dome 54 can be formed at the top of the container 10. The dome 54 can then be removed during further processing.

Further, each mold half 32, 34 can further define a second cavity (not shown) for simultaneously molding a second container (not shown). The second cavity can be molded 180-degrees opposed to the first container 10 and connected to the first container across the dome 54. After extraction of the connected containers, the containers can then be separated at the area comprising the dome 54 and the remnants of the dome 54 can be removed from the respective containers.

The plastic material parison 50 can comprise a single layer plastic or a multi-layer plastic. The plastic can be chosen from any suitable material, including but not limited to polyvinylchloride, polyethyleneterephthalate, high density polyethylene, polycarbonate, polystyrene and polypropylene plastic materials which are particularly suited for containers 10 having cold fill food items. Further, a multi-layer plastic may be used which has a barrier layer, such as an oxygen barrier layer, comprising, for example, a material including, but not limited to polyvinylidenechloride, nylon, and ethylenevinylalcohol copolymer. An oxygen barrier layer is particularly suited for containers 10 having oxygen sensitive food items. As mentioned previously, in addition, a barrier quality can be provided by spray coating the molded container. Plasma deposition may also be used to create a barrier layer. In addition to oxygen, such a barrier may also be intended for odors, solvents or other gases.

The narrow mid-section 20 of the sidewall 12 provides an area for which it is easy for a user to grip the container 10. The mid-section 20 provides an indentation in which normal sized adult fingers can fit thereby enabling a more secure grip about the mid-section 20 as the upper and lower frustum sections 22, 18 respectively will hinder the container 10 for moving upward or downward relative to the fingers. This is particularly useful when the exterior of the container 10 is wet due to sweating or condensation or when the container 10 is hot.

The container 10 can be filled with any suitable material. In a preferred embodiment, the container 10 is suitable for food products, such as, for example, salsa, beans, cheese or sauces. The container 10 can be filled with material by cold-fill or hot-fill processes or, the container 10 can be used in a retort process as well. The container 10 is equally adaptable for or usable in such varied processes/applications because of the inherent integrity and sturdiness provided by the overall shape of the container 10. With this hourglass-like shape, the walls resist paneling and other deformations during a retort process in which items are first sealed in the container prior to being subjected to a heating process followed by a cooling process.

After the container 10 is filled with a suitable material, the upper rim 14 of the container can be sealed with a suitable sealing member such as a film or foil which is bonded to the upper rim 14. In the alternative, an overseal (not shown) can be placed over the lid 24. The overseal can be formed over the lid 14, recess 26 and a portion of the upper frustum section 22 and secured in place by a shrink wrap process. A sealing member secured to the upper rim 14 can comprise any conventional sealing material, such as, for example, a single layer or multiple layer foil.

For retort processes, the container 10 can be filled with material at an ambient temperature or an elevated temperature for materials where it is desired to reduce the viscosity of the material for handling or filling purposes.

Again, while a two mold formation has been discussed and shown, containers of this type can be made using more than two mold parts, e.g., three or four mold sections. Specifically, Figures 9 and 10 illustrate alternative containers 10a and 60 respectively that are both surrounded by three-piece molds 62, 64 respectively. Specifically, the three-piece mold 62 includes upper sections 66, 68 and lower section 70. The three-piece mold 64 includes upper sections 72, 76 and lower section 78. The container 10a is fitted with three bottom feet 80, 82 and 86 as further illustrated in Figure 8. All other structural features of the container 10a are described above with respect to Figures 1 and 3. The container 60 illustrated in Figure 10 was first disclosed in U.S. Patent Application No. 09/543,949 filed on April 6, 2000, the entirety of which is incorporated herein by reference.

From the above description it is apparent that the objects of the present invention have been achieved. While only certain embodiments have been set forth, alternative embodiments and various modifications will be apparent from the above description to those skilled in the art. These and other alternatives are considered equivalents and within the spirit and scope of the present invention.

WHAT IS CLAIMED IS:

1. A plastic molded container comprising:

a bowl comprising an upper rim, a bottom and a sidewall extending between the upper rim and the bottom,

5 the sidewall comprising a lower frustum section, a narrow mid-section and an upper frustum section,

the lower frustum section connecting the bottom to the mid-section, the lower frustum section decreasing in width as the lower frustum section extends from the bottom to mid-section,

10 the upper frustum section connecting the upper rim to the mid-section, the upper frustum section decreasing in width as the upper frustum section extends from the upper rim to mid-section.

2. The plastic molded container of claim 1 further comprising a lid securable to the upper rim.

15 3. The plastic molded container of claim 2 further comprising a recess disposed between the upper frustum section and the upper rim,

the lid further comprising a lower lip,

the recess for receiving the lower lip of the lid.

20 4. The plastic molded container of claim 1 wherein the lid is rotatably securable to the rim.

25 5. The plastic molded container of claim 1 wherein the container is molded from a plastic selected from the group consisting of polyvinylchloride, polyethyleneterephthalate, high density polyethylene, polycarbonate, polystyrene and polypropylene.

6. The plastic molded container of claim 1 wherein the container is blow-molded from a single layer plastic.

30 7. The plastic molded container of claim 1 wherein the container is blow-molded from a multi-layer plastic.

8. The plastic molded container of claim 7 wherein said multi-layer plastic further comprises at least one gas barrier layer selected from the group consisting of polyvinylidenechloride, nylon, and ethylenevinylalcohol copolymer.

5 9. The plastic molded container of claim 1 wherein the container has a diameter and a height, the diameter being greater than the height.

10 10. The plastic molded container of claim 1 wherein the bottom comprises a downwardly extending circular standing ridge.

10 11. A method of forming a plastic container comprising the steps of:
providing two mold halves, each mold half having a cavity defining one-half of the container which comprises a bowl comprising an upper rim, a bottom and a sidewall extending between the upper rim and the bottom, the sidewall comprising a lower frustum section, a narrow mid-section and an upper frustum section, the lower frustum section connecting the bottom to the mid-section, the lower frustum section decreasing in width as the lower frustum section extends from the bottom to mid-section, the upper frustum section connecting the upper rim to the mid-section, the upper frustum section decreasing in width as the upper frustum section extends from the upper rim to mid-section;

20 abutting the two mold halves together;

blowing plastic material into the abutted mold halves under blow molding conditions;

separating the mold halves; and

extracting the resultant container.

25 12. The method of claim 11 wherein the plastic material is selected from the group consisting of polyvinylchloride, polyethyleneterephthalate, high density polyethylene, polycarbonate, polystyrene and polypropylene.

30 13. The method of claim 11 wherein the plastic material comprises a single layer plastic.

14. The method of claim 11 wherein the plastic material comprises a multi-layer plastic.

15. The method of claim 14 wherein said multi-layer plastic further comprises at least one gas barrier layer selected from the group consisting of polyvinylidenechloride, nylon, and ethylenevinylalcohol copolymer.

5 16. The method of claim 11 wherein the container has a diameter and a height, the diameter being greater than the height.

17. The method of claim 11 wherein the bottom comprises a downwardly extending circular standing ridge.

10 18. A method of forming a plastic container comprising the steps of:
providing a three piece mold, each mold piece having a cavity defining one-third of the container which comprises a bowl comprising an upper rim, a bottom and a sidewall extending between the upper rim and the bottom, the sidewall comprising a lower frustum section, a narrow mid-section and an upper frustum section, the lower frustum section connecting the bottom to the mid-section, the lower frustum section decreasing in width as the lower frustum section extends from the bottom to mid-section, the upper frustum section connecting the upper rim to the mid-section, the upper frustum section decreasing in width as the upper frustum section extends from the upper rim to mid-section;

15 abutting the three mold pieces together;

blowing plastic material into the abutted mold pieces under blow molding conditions;

separating the mold pieces; and

extracting the resultant container.

20 19. A method of hot-filling a container, comprising the steps of:
providing a plastic container comprising a bowl comprising an upper rim, a bottom and a sidewall extending between the upper rim and the bottom, the sidewall comprising a lower frustum section, a narrow mid-section and an upper frustum section, the lower frustum section connecting the bottom to the mid-section, the lower frustum section decreasing in width as the lower frustum section extends from the bottom to mid-section, the upper frustum section connecting the upper rim to the mid-section, the upper frustum section decreasing in width as the upper frustum section extends from the upper rim to mid-section;




25 positioning the container within a receptacle;




filling the container with material under hot filling conditions;
sealing the container with a suitable seal member; and
securing a lid on the container.

- 5 20. A method of retorting material disposed within a container, comprising the steps of:
 providing a plastic container comprising a bowl comprising an upper rim, a bottom and a
 sidewall extending between the upper rim and the bottom, the sidewall comprising a lower frustum
 section, a narrow mid-section and an upper frustum section, the lower frustum section connecting
 the bottom to the mid-section, the lower frustum section decreasing in width as the lower frustum
10 section extends from the bottom to mid-section, the upper frustum section connecting the upper rim
 to the mid-section, the upper frustum section decreasing in width as the upper frustum section
 extends from the upper rim to mid-section;
 positioning the container within a receptacle;
 filling the container with material under ambient or near ambient conditions;
 securing a lid on the container;
 sealing the container with a suitable seal member;
 heating the container, material, lid and seal member.

ABSTRACT OF THE DISCLOSURE

A molded plastic container with a sidewall having a general hourglass configuration. The container structure includes an upper rim, a bottom and a sidewall that extends between the upper rim and the bottom. The sidewall includes a lower frustum section, a narrow mid-section and an upper frustum section. The lower frustum section connects the bottom to the narrow mid-section and decreases in width as it extends from the bottom to the narrow mid-section. The upper frustum section extends from the upper rim to the narrow mid-section and decreases in width as it extends from the upper rim to the mid-section. A method of making such a container, a method of hot-filling such a container and a method of retorting material enclosed in such a container are also disclosed.





**CONTINUATION-IN-PART
DECLARATION AND POWER OF ATTORNEY**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and joint inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled:

"MOLDABLE PLASTIC CONTAINER WITH HOURGLASS PROFILE"

Case No. P00,0677 the specification of which

is a continuation-in-part application of U.S. Serial No. 09/543,949 filed on April 6, 2000.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment specifically referred to in the oath or declaration.

I acknowledge the duty to disclose to the United States Patent Office all information known to me, which information is material to the examination of this application, in accordance with Title 37, Code of Federal Regulations, 1.56¹. I also acknowledge the duty to disclose to the United States Patent Office all information known to me to be material to patentability as defined in §1.56 which became available between the filing date of the prior application April 6, 2000 and the filing date of this continuation-in-part application.

As to the subject matter of this application which is common to U.S. Serial No. 09/543,949 filed on April 6, 2000, I do not know and do not believe that this invention was ever known or used in the United States of America before my or our invention thereof, or patented or described in any printed publication in any country before my or our invention thereof or more than one year prior to the earlier application, I believe that the same was not in public use or on sale in the United States of America more than one year prior to this earlier application, and I believe that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this earlier application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months prior to this earlier application, and that no application for patent or inventor's certificate on this invention has been filed in any country foreign to the United States of America prior to this earlier application by me or my legal representatives or assigns, except as identified below.

¹(b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and

(1) It establishes, by itself or in combination with other information, a *prima facie* case of unpatentability of a claim; or

(2) It refutes, or is inconsistent with, a position the applicant takes in:

(i) Opposing an argument of unpatentability relied on by the Office, or

(ii) Asserting an argument of unpatentability.

A *prima facie* case of unpatentability is established when the information compels a conclusion that a claim is unpatentable under the preponderance of evidence, burden-of-proof standard, giving each term in the claim its broadest reasonable construction consistent with the specification, and before any consideration is given to evidence which may be submitted in an attempt to establish a contrary conclusion of patentability.

As to the subject matter of this application which is not common to **U.S. Serial No. 09/543,949 on April 6, 2000**, I do not know and do not believe this invention was ever known or used in the United States of America before my or our invention thereof, or patented or described in any printed publication in any country before my or our invention thereof or more than one year prior to this application, I believe that the same was not in public use or on sale in the United States of America more than one year prior to this application, and I believe that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months prior to this application, and that no application for patent or inventor's certificate on this invention has been filed in any country foreign to the United States of America prior to this application by me or my legal representatives or assigns, except as identified below.

I hereby claim foreign priority benefits under Title 35, United States Code, 119 of any foreign application(s) for patent or inventor's certificate listed below:

Number	Prior Foreign Application(s) Country	Date
--------	---	------

and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the above listed application on which priority is claimed:

Number	Prior Foreign Application(s) Country	Date
--------	---	------

If no priority is claimed, I have identified all foreign patent applications filed prior to this application:

Number	Prior Foreign Application(s) Country	Date
--------	---	------

And I hereby appoint Messrs. John D. Simpson (Registration No. 19,842), Dennis A. Gross (24,410), Robert M. Barrett (30,142), Steven H. Noll (28,982), Kevin W. Guynn (29,927), Robert M. Ward (26,517), Brett A. Valiquet (27,841), Edward A. Lehman (22,312), David R. Metzger (32,919), Todd S. Parkhurst (26,494), James D. Hobart (24,149), Melvin A. Robinson (31,870), Joseph P. Reagen (35,332), Michael R. Hull (35,902), Michael S. Leonard (37,557), William E. Vaughan (39,056) and Lewis T. Steadman (17,074) all members of the firm of Hill & Simpson, A Professional Corporation

Telephone: 312/876-0200

my attorneys with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith and direct that all correspondence be forwarded to:

Hill & Simpson
A Professional Corporation
85th Floor Sears Tower
233 South Wacker Drive
Chicago, Illinois 60606

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor GROVER JOHN MANDERFIELD, JR.
Inventor's signature *Grover John Manderfield Jr* Date 6/13/00
Residence Mt. Prospect, Illinois 60056
Citizenship United States
Post Office Address 101 South Elm Street, Mt. Prospect, Illinois 60056

Full name of second inventor TED L. BEAVER
Inventor's signature *Ted L Beaver* Date 6/13/00
Residence Roselle, Illinois 60172
Citizenship United States
Post Office Address 11 West Forest Avenue, Roselle, Illinois 60172

Full name of third inventor _____
Inventor's signature _____ Date _____
Residence _____
Citizenship _____
Post Office Address _____